

Shenzhen Yofolon Electronic Co., LTD

## AC Fan Specification List

SPECIFICATIONS:80x80x25mm AC FAN										
Model No.	Bearing Type Ball & Sleeve	Frequency	Rated Voltage	Rated Current	Input Power	Speed	Air Flow	Static Pressure	Noise	Weight
	(B/S)	(Hz)	(V)	(A)	(W)	(RPM)	(CFM)	(mmH <sub>2</sub> O)	dB(A)	(g)
AC8025S11H	S	60	115~125	0.10	11.50	2800	22.50	4.83	33.25	208
AC8025S11M	S			0.09	10.35	2400	19.50	3.45	30.56	
AC8025S11L	S			0.08	9.20	2200	17.20	2.60	26.47	
AC8025B11H	B			0.10	11.50	2800	22.50	4.83	33.25	
AC8025B11M	B			0.09	10.35	2400	19.50	3.45	30.56	
AC8025B11L	B			0.08	9.20	2200	17.20	2.60	26.47	
AC8025S22H	S	50	220~240	0.10	22.00	2400	19.50	3.45	30.56	
AC8025S22M	S			0.08	17.60	2200	17.20	2.60	26.47	
AC8025S22L	S			0.06	13.20	2000	15.00	2.35	22.55	
AC8025B22H	B			0.10	22.00	2400	19.50	3.45	30.56	
AC8025B22M	B			0.08	17.60	2200	17.20	2.60	26.47	
AC8025B22L	B			0.06	13.20	2000	15.00	2.35	22.55	
AC8025S38H	S	50	380	0.07	26.60	2300	18.50	3.30	29.60	
AC8025B38H	B			0.07	26.60	2300	18.50	3.30	29.60	

Notes: Specificatiions subject to change without notice!



Model No.	Bearing Type Ball & Sleeve	Frequency	Rated Voltage	Rated Current	Input Power	Speed	Air Flow	Static Pressure	Noise	Weight
	(B/S)									
AC8038S11H	S	60	115~125	0.13	15.00	2800	30.25	5.36	34.50	340
AC8038S11M	S			0.11	12.65	2400	23.50	4.86	31.50	
AC8038S11L	S			0.09	10.35	2000	19.25	2.75	29.63	
AC8038B11H	B			0.13	15.00	2800	30.25	5.36	34.50	
AC8038B11M	B			0.11	12.65	2400	23.50	4.86	31.50	
AC8038B11L	B			0.09	10.35	2000	19.25	2.75	29.63	
AC8038S22H	S	50	220~240	0.11	24.20	2400	23.50	4.86	31.50	
AC8038S22M	S			0.09	19.80	2200	21.64	3.15	30.54	
AC8038S22L	S			0.08	17.60	2000	19.25	2.75	29.63	
AC8038B22H	B			0.11	24.20	2400	23.50	4.86	31.50	
AC8038B22M	B			0.09	19.80	2200	21.64	3.15	30.54	
AC8038B22L	B			0.08	17.60	2000	19.25	2.75	29.63	
AC8038S38H	S	50	380	0.09	34.20	2400	23.50	4.86	31.50	
AC8038B38H	B			0.09	34.20	2400	23.50	4.86	31.50	
Notes: Specificatiions subject to change without notice!										



## SPECIFICATIONS:92x92x25mm AC FAN

Model No.	Bearing Type Ball & Sleeve	Frequency	Rated Voltage	Rated Current	Input Power	Speed	Air Flow	Static Pressure	Noise	Weight
	(B/S)	(Hz)	(V)	(A)	(W)	(RPM)	(CFM)	(mmH <sub>2</sub> O)	dB(A)	(g)
AC9225S11H	S	60	115~125	0.11	12.65	2900	37.50	5.68	37.00	240
AC9225S11M	S			0.09	10.35	2600	30.00	5.15	33.00	
AC9225S11L	S			0.07	8.05	2300	23.20	2.95	26.00	
AC9225B11H	B			0.11	12.65	2900	37.50	5.68	37.00	
AC9225B11M	B			0.09	10.35	2600	30.00	5.15	33.00	
AC9225B11L	B			0.07	8.05	2300	23.20	2.95	26.00	
AC9225S22H	S	50	220~240	0.10	22.00	2500	29.25	3.35	32.50	
AC9225S22M	S			0.08	17.60	2300	23.20	2.95	26.00	
AC9225S22L	S			0.06	13.20	2000	20.12	2.70	22.50	
AC9225B22H	B			0.10	22.00	2500	29.25	3.35	32.50	
AC9225B22M	B			0.08	17.60	2300	23.20	2.95	26.00	
AC9225B22L	B			0.06	13.20	2000	20.12	2.70	22.50	
AC9225S38H	S	50	380	0.07	26.60	2500	29.25	3.35	32.50	
AC9225B38H	B			0.07	26.60	2500	29.25	3.35	32.50	

Notes: Specifications subject to change without notice!



Model No.	Bearing Type Ball & Sleeve	Frequency	Rated Voltage	Rated Current	Input Power	Speed	Air Flow	Static Pressure	Noise	Weight	
	(B/S)										(Hz)
AC9238S11H	S	60	115~125	0.14	16.10	2800	48.20	5.86	36.20	350	
AC9238S11M	S			0.11	12.65	2400	43.00	5.24	31.50		
AC9238S11L	S			0.09	10.35	2000	26.55	3.35	25.30		
AC9238B11H	B			0.14	16.10	2800	48.20	5.86	36.20		
AC9238B11M	B			0.11	12.65	2400	43.00	5.24	31.50		
AC9238B11L	B			0.09	10.35	2000	26.55	3.35	25.30		
AC9238S22H	S	50	220~240	0.12	26.40	2400	43.00	5.24	31.50		
AC9238S22M	S			0.10	22.00	2200	28.15	3.50	27.00		
AC9238S22L	S			0.08	17.60	1800	24.24	3.00	23.00		
AC9238B22H	B			0.12	26.40	2400	43.00	5.24	31.50		
AC9238B22M	B			0.10	22.00	2200	28.15	3.50	27.00		
AC9238B22L	B			0.08	17.60	1800	24.24	3.00	23.00		
AC9238S38H	S	50	380	0.09	34.20	2400	43.00	5.24	31.50		
AC9238B38H	B			0.09	34.20	2400	43.00	5.24	31.50		
Notes: Specificatiions subject to change without notice!											



## SPECIFICATIONS:120x120x25mm AC FAN

Model No.	Bearing Type Ball & Sleeve	Frequency	Rated Voltage	Rated Current	Input Power	Speed	Air Flow	Static Pressure	Noise	Weight
	(B/S)	(Hz)	(V)	(A)	(W)	(RPM)	(CFM)	(mmH <sub>2</sub> O)	dB(A)	(g)
AC1225S11H	S	60	115~125	0.18	20.70	2400	78.00	4.10	40.00	370
AC1225S11M	S			0.15	17.25	2000	58.00	3.20	35.00	
AC1225S11L	S			0.11	12.65	1700	48.00	2.65	29.00	
AC1225B11H	B			0.18	20.70	2400	78.00	4.10	40.00	
AC1225B11M	B			0.15	17.25	2000	58.00	3.20	35.00	
AC1225B11L	B			0.11	12.65	1700	48.00	2.65	29.00	
AC1225S22H	S	50	220~240	0.09	19.80	2200	66.20	3.56	38.00	
AC1225S22M	S			0.07	15.40	2000	58.00	3.20	35.00	
AC1225S22L	S			0.05	11.00	1800	50.00	2.74	30.00	
AC1225B22H	B			0.09	19.80	2200	66.20	3.56	31.50	
AC1225B22M	B			0.07	15.40	2000	58.00	3.20	27.00	
AC1225B22L	B			0.05	11.00	1800	50.00	2.74	23.00	
AC1225S38H	S	50	380	0.06	22.80	2200	66.20	3.56	38.00	
AC1225B38H	B			0.06	22.80	2200	66.20	3.56	38.00	

Notes: Specifications subject to change without notice!



## SPECIFICATIONS:120x120x38mm AC FAN

Model No.	Bearing Type Ball & Sleeve	Frequency	Rated Voltage	Rated Current	Input Power	Speed	Air Flow	Static Pressure	Noise	Weight
	(B/S)	(Hz)	(V)	(A)	(W)	(RPM)	(CFM)	(mmH <sub>2</sub> O)	dB(A)	(g)
AC1238S11H	S	60	115~125	0.18	20.70	2900	110.00	7.60	44.60	540
AC1238S11M	S			0.15	17.25	2200	70.50	5.00	36.00	
AC1238S11L	S			0.12	11.50	1800	60.20	4.50	29.50	
AC1238B11H	B			0.18	20.70	2900	110.00	7.60	44.60	
AC1238B11M	B			0.15	17.25	2200	70.50	5.00	36.00	
AC1238B11L	B			0.12	11.50	1800	60.20	4.50	29.50	
AC1238S22H	S	50	220~240	0.12	26.40	2700	96.50	6.40	40.00	
AC1238S22M	S			0.09	19.80	2400	75.60	5.60	37.00	
AC1238S22L	S			0.08	17.60	2000	66.00	4.80	31.60	
AC1238B22H	B			0.12	26.40	2700	96.50	6.40	40.00	
AC1238B22M	B			0.09	19.80	2400	75.60	5.60	37.00	
AC1238B22L	B			0.08	17.60	2000	66.00	4.80	31.60	
AC1238S38H	S	50	380	0.07	26.60	2600	91.00	6.35	39.00	
AC1238B38H	B			0.07	26.60	2600	91.00	6.35	39.00	


Notes: Specifications subject to change without notice!



## SPECIFICATIONS:150x150x50mm AC FAN

Model No.	Bearing Type Ball & Sleeve	Frequency	Rated Voltage	Rated Current	Input Power	Speed	Air Flow	Static Pressure	Noise	Weight
	(B/S)	(Hz)	(V)	(A)	(W)	(RPM)	(CFM)	(mmH <sub>2</sub> O)	dB(A)	(g)
AC1550S11H	S	60	115~125	0.45	51.75	3000	210.00	17.20	49.00	550
AC1550S11M	S			0.38	43.70	2300	160.00	14.00	40.00	
AC1550S11L	S			0.32	36.80	1500	105.00	6.10	30.50	
AC1550B11H	B			0.45	51.75	3000	210.00	17.20	49.00	
AC1550B11M	B			0.38	43.70	2300	160.00	14.00	40.00	
AC1550B11L	B			0.32	36.80	1500	105.00	6.10	30.50	
AC1550S22H	S	50	220~240	0.22	48.40	2700	190.00	15.80	45.50	
AC1550S22M	S			0.19	41.80	2400	170.00	14.80	41.50	
AC1550S22L	S			0.16	35.20	2000	130.00	8.50	37.00	
AC1550B22H	B			0.22	48.40	2700	190.00	15.80	45.50	
AC1550B22M	B			0.19	41.80	2400	170.00	14.80	41.50	
AC1550B22L	B			0.16	35.20	2000	130.00	8.50	37.00	
AC1550S38H	S	50	380	0.11	41.80	2700	190.00	15.80	45.50	
AC1550B38H	B			0.11	41.80	2700	190.00	15.80	45.50	

Notes: Specifications subject to change without notice!



Notes: Specifications subject to change without notice!





## SPECIFICATIONS:D220x60mm AC FAN

Model No.	Bearing Type Ball & Sleeve	Frequency	Rated Voltage	Rated Current	Input Power	Speed	Air Flow	Static Pressure	Noise	Weight
	(B/S)	(Hz)	(V)	(A)	(W)	(RPM)	(CFM)	(mmH <sub>2</sub> O)	dB(A)	(g)
AC2260B11H	B	60	115~125	0.80	92.00	2800	405.00	27.50	66.00	1450
AC2260B11M	B			0.45	51.75	2400	360.00	24.30	57.00	
AC2260B22H	B	50	220~240	0.35	77.00	2800	405.00	27.50	66.00	
AC2260B22M	B			0.28	61.60	2400	360.00	24.30	57.00	
AC2260B38H	B	50	380	0.16	60.80	2800	405.00	27.50	66.00	
AC2260B38M	B			0.12	45.60	2400	360.00	24.30	57.00	

Notes: Specifications subject to change without notice!

**YOFOLON****SPECIFICATIONS:D254x89mm AC FAN**

Model No.	Bearing Type Ball & Sleeve	Frequency	Rated Voltage	Rated Current	Input Power	Speed	Air Flow	Static Pressure	Noise	Weight
	(B/S)	(Hz)	(V)	(A)	(W)	(RPM)	(CFM)	(mmH <sub>2</sub> O)	dB(A)	(g)
AC2589B11H	B	60	115~125	0.90	103.50	2600	830.00	20.20	80.00	2300
AC2589B11M	B			0.70	80.50	2200	705.00	11.50	65.00	
AC2589B22H	B	50	220~240	0.40	88.00	2600	830.00	20.20	80.00	
AC2589B22M	B			0.30	66.00	2200	705.00	11.50	65.00	
AC2589B38H	B	50	380	0.24	91.20	2600	830.00	20.20	80.00	
AC2589B38M	B			0.18	68.40	2200	705.00	11.50	65.00	

Notes: Specifcations subject to change without notice!